



5820F24

6.3mm (.250) UP-TP Terminals



Description TP Low insertion flag for tab 6,3x0,8
Wire section range 0.20-0.60 mm² (AWG 24-20)
Max. Insulator Ø 2.1 mm.

Material Nickel-plated Steel, 0.4 mm thickness

Wire section	Current
*0.20 mm ²	N/A *
*0.35 mm ²	N/A *
0.50 mm ²	8 A
0.60 mm ²	8 A

Note: Current carrying capacity with maximal suitable wire size (IEC 760)
 * N/A IEC760

Max. Voltage -

Note: Depending on housing material.

Max. Contact resistance 2.08 mΩ

Note: Maximal contact resistance with minimal suitable wire size (IEC 760)


Max. Temperature 300°C

Note: As per DIN 61210 standard.

Thermal derating (see graph →)

Insertion/Withdrawal forces

	ESCUBEDO
1st. Insertion	35 N Max
1st. Withdrawal	30±60 N
6th. Withdrawal	22 N Min



Thermal derating curves
Note: 20% security margin is applied.

Application tool MN5820F

Wire striping length 4.4 (±0.5) mm


Crimping parameters & Pull out force

Wire section (mm ²)	Conductor (±0,03)		Insulator (±0,10)	Pull-out force	
	Height (mm.)	Width (mm.)	Width (mm.)	DIN46249	Measured
0.20	1.10	1.95	3.15	-	> 40 N
0.35	1.15	1.97	3.15	-	> 60 N
0.50	1.25	1.97	3.15	≥ 80 N	> 85 N
0.60	1.30	1.98	3.15	≥ 80 N	> 110 N

Note: Values only valid for the application tool specified upwards. The insulator widths are only indicative as they are dependent on the sheath thickness of the wire used.

Packaging 4000 Pieces on 20 mm. cardboard reel, 19.5 mm terminal chain pitch

Drawing



Approvals

- RoHS Compliant



Document History

Rev. Nr.	Modification	Date	Created/Revised	Approved
1	Creation	13/03/2012	D.Martinez	A.Calvet
2	Insertion and withdrawal force update	04/09/2013	David Martinez	Adam Calvet

Disclaimer

Data obtained from Escubedo Laboratory essays, using own methodology, cabling and equipment, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is published only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview. For further information please visit our web site or contact us.